

Power supply:	230 VAC +10/-15 % 47-63 Hz 115 VAC +10/-15 % 47-63 Hz (on request)
Power consumption:	Max. 30 VA
Digital outputs:	3 fuel valves max. 1 A cos $\phi$ 0,4 VL fan max. 2 A cos $\phi$ 0,4 oil pump max. 2 A cos $\phi$ 0,4 ignition transformer alarm output
Housing:	Polycarbonate + ABS
Weight:	1,0 kg
Approvals:	<p>EC Type Examination Certificate (Module B) according to Directive 2014/68/EU  DIN EN 298:2012  DIN EN 13611:2011  DIN EN 1643:2001  DIN EN 12067-2:2004  ISO 23552-1  DIN EN 50156-1, No. 10.5</p> <p>EC Type Examination Certificate according to 2009/142/EC (Gas Appliance Directive)  DIN EN 298  DIN EN 13611  DIN EN 1643  DIN EN 12067-2</p> <p>SIL 3 Confirmation  DIN EN 61508 Part 1-7 (BT331, BT341)</p> <p>CE Declaration of Conformity  2014/35/EU (Low Voltage Directive)  2014/30/EU (EMC Directive)  2014/68/EU (Pressure Equipment Directive Cat. 4 Mod. B+D)  2009/142/EC (Gas Appliance Directive)</p> <p>MH48669  Controls, Primary Safety Certified for Canada, Component  UL 372  UL 1998</p>

