





Power supply:	240 VAC / 24 VDC
Ambient temperature during operation:	-30 °C ... +70° C
Ambient temperature transportation:	-40 °C ... +80° C
Anzahl Stellantriebe/ Stellglieder*:	10
Resolution:	0,1% of the angle of rotation
Run time of the actuators:	60 s
Digital Input*:	60
Analogue Input*:	18 (9 failsafe)
Digital Output*:	41
Analogue Output*:	0/4 ... 20 mA
Load:	150 Ω
Number of curve sets (profiles)*:	16
BUS connection:	Modbus TCP on-board
Approvals:	<p>EC Type Examination Certificate according to 2014/68/EU (Pressure Equipment Directive)</p> <p> DIN EN 298 DIN EN 1643 DIN EN 12067 ISO 23552-1 DIN EN 60730-2-5 DIN EN 13611 DIN EN 60730</p> <p> EC Type Examination Certificate according to 2016/426/EU (Gas Appliance Directive)</p> <p> DIN EN 298 DIN EN 12067-2 DIN EN 1643 SIL 3 Confirmation</p> <p> CE Declaration of Conformity 2014/35/EU (Low Voltage Directive) 2014/30/EU (EMC Directive) 2014/68/EU (Pressure Equipment Directive Cat. 4 Mod. B+D) 2016/426/EU (Gas Appliance Directive) 2011/65/EU (RoHS)</p>

*Refers to maximum extension